KH20-**31**



Bone Conductor - Data Sheet

Mechanical Data

- Weight approx. 10 g
 Dimensions Length: 24.35 mm
 Width: 19.25 mm
 - Height: 14.75 mm
- Housing Colours Different Colours
- Connection
 2-pin (acc. DIN IEC 60118-12)

Electrical Data

- DC Resistance
- Nominal Impedance @ 1 kHz
- Max. Output (@ 1 V const.)
- Sensitivity (@ 1 V const.)

Frequency Response


88 Ohm ± 10 % 300 Ohm ± 20 % 109 dB OVFL ± 3 dB @ 650 Hz 103 dB OVFL ± 3 dB @ 1 kHz



Measuring Conditions

- Artificial Mastoid Brüel & Kjaer 4930 with static force 2.5 N
- 1 V constant supply
- Compensation for the transmission through the Artificial Mastoid via post processing of all measurements

Impedance Curve



QUALITY MANUFACTURED IN AUSTRIA

Changes may be done without any notice in order to improve product performance.

120

110 100 100 100 1000 1000 Frequency [Hz]

Warnings

- In order to avoid possible damage, the fitting of the device must be carried out by an authorized hearing aid expert!
- Swallowing of Bone Conductors may be hazardous to your health and may cause severe injuries and even death!
- Keep Bone Conductor, which you have taken off, out of reach of other persons or children!
- For extra hygienic and skin-protective cleaning, special cleaning products must be used!

Design and performance by BHM-Tech – All rights reserved.

A quality product of BHM-Tech Produktionsgesellschaft mbH, Grafenschachen 242, 7423 Grafenschachen, Austria / www.bhm-tech.at